173 Vistawood Aqua Wood Putty

Vistawood Aqua Ahşap Macunu

PRODUCT DESCRIPTION

Fast-drying, easy-to-sand water-based wood putty with high filling power.

AREAS OF USE

Filling cracks, holes, nail marks and joints in wood, MDF and chipboard.

TECHNICAL PROPERTIES

Components	Single-component (1K)
Colour	White and wood shades
Density (20 °C)	1.75 ± 0.05 kg/L
Volume solids	70% ± 3
Theoretical coverage	1 m²/kg (single coat)
Application method	Spatula, trowel
Thinning	Ready to use, do not thin
Number of coats	Thin layers as required
Equipment cleaning	Water

DRYING TIMES

Sandable	2–4 hours (depending on thickness)
Paintable	24 hours

Values apply at 23 °C ambient temperature and 50% relative humidity; low temperatures and high humidity extend the times.

SURFACE PREPARATION

Wood must be clean, dry (moisture < 15%) and free from dust. Sand off old, loose paint and varnish; wipe resinous areas with thinner. Sand along the grain and remove dust.

APPLICATION CONDITIONS

Application and surface temperature: +5 °C to +35 °C. Do not apply in direct sunlight, rain, strong wind or when there is a risk of frost.

PACKAGING

600 g · 1.35 kg · 4 kg · 25 kg

STORAGE AND SHELF LIFE

Store in tightly closed original packaging at +5 °C to +35 °C in a cool, dry place. Protect from frost and direct sunlight. In unopened original packaging, from the date of manufacture: 24 months.

HEALTH AND SAFETY

Before use, read the product Safety Data Sheet (SDS) and the hazard and precautionary statements on the label. Ensure adequate ventilation during application; wear suitable protective gloves, goggles and, where necessary, a mask. Keep out of reach of children. Do not empty product residues or containers into drains; dispose of them in accordance with local regulations.

The information in this technical data sheet is based on laboratory tests and practical experience. As application conditions, substrates and equipment are beyond our control, the user must verify the suitability of the product for the intended application. GENAŞ Gen Boya San. ve Tic. A.Ş. is responsible only for the quality of the product and cannot be held liable for uses other than those recommended. This sheet remains valid until superseded; we reserve the right to change product specifications in line with technological developments.