143 Vistawood Aqua Exterior Wood Varnish

Vistawood Aqua Dış Cephe Ahşap Vernik

PRODUCT DESCRIPTION

UV-resistant, water-repellent, water-based varnish for exterior wooden surfaces.

AREAS OF USE

Wooden cladding, pergolas, fences, garden furniture, doors and window frames.

FEATURES

- Preserves the natural grain of wood
- UV and weather resistance
- Water-repellent, breathable film
- Low odour, easy clean-up

TECHNICAL PROPERTIES

Components	Single-component (1K)
Colour	Stock colours: 1801 Transparent, 1802 Chestnut, 1803 Dark Oak, 1804 Hazelnut, 1806 Mahogany, 1807 Antique Black, 1809 Green, 1818 Burma, 1821 Light Oak, 1825 Tobacco, 1839 Walnut, 1873 Teak
Gloss	Silk matt
Density (20 °C)	1.25 ± 0.05 kg/L
Volume solids	35% ± 3
Theoretical coverage	14 m²/L (single coat)
Application method	Brush, roller, spray
Thinning	Ready to use; if needed max. 5–10% water
Number of coats	2–3 coats
Equipment cleaning	Water

DRYING TIMES

Touch dry	1 hour
Recoat	4–6 hours
Fully dry	24 hours

Values apply at 23 °C ambient temperature and 50% relative humidity; low temperatures and high humidity extend the times.

SURFACE PREPARATION

Wood must be clean, dry (moisture < 15%) and free from dust. Sand off old, loose paint and varnish; wipe resinous areas with thinner. Sand along the grain and remove dust.

APPLICATION CONDITIONS

Application and surface temperature: +5 °C to +35 °C. Do not apply in direct sunlight, rain, strong wind or when there is a risk of frost.

PACKAGING

750 ml · 2.5 L · 15 L

STORAGE AND SHELF LIFE

Store in tightly closed original packaging at +5 °C to +35 °C in a cool, dry place. Protect from frost and direct sunlight. In unopened original packaging, from the date of manufacture: 24 months.

HEALTH AND SAFETY

Before use, read the product Safety Data Sheet (SDS) and the hazard and precautionary statements on the label. Ensure adequate ventilation during application; wear suitable protective gloves, goggles and, where necessary, a mask. Keep out of reach of children. Do not empty product residues or containers into drains; dispose of them in accordance with local regulations.

The information in this technical data sheet is based on laboratory tests and practical experience. As application conditions, substrates and equipment are beyond our control, the user must verify the suitability of the product for the intended application. GENAŞ Gen Boya San. ve Tic. A.Ş. is responsible only for the quality of the product and cannot be held liable for uses other than those recommended. This sheet remains valid until superseded; we reserve the right to change product specifications in line with technological developments.